



# UT-509D RS-485/RS-422

UT-509D RS-422 RS-485 RS-422/  
RS-485 RS-422/RS-485  
DC/DC 2500Vrms

RS-422/RS-485 TVS TRANSIENT  
VOLTAGE SUPPRESSOR TVS  
TVS

600W LIGHTNING ESD  
RS-422/RS-485

RS-422 RS-485 I/O  
( RTS DTR )

(RS-422) (RS-485)  
UT-509D 128 RS-422 RS-485  
300bps-115.2Kbps

1 EIA/TIA RS-485/RS-422  
2 RS-422/RS-485 5PIN

3 RS-422 RS-485 600W  
u 15KV ESD  
4 2500Vrms 500DC DC/DC  
5  
6  
7 PWR TXD  
RXD  
8  
9 300bps-115.2Kbps  
10 110mm×80mm×25mm  
11 -40 85 5%RH 95%RH  
12 0-5000 115200bps-9600bps

## RS-485/RS-422

(PIN)		RS-422	RS-485
1	T/R+	(A+)	RS-485 (A+)
2	T/R-	(B-)	RS-485 (B-)
3	RXD+	(A+)	
4	RXD-	(B-)	
5	GND1		

## RS-485/RS-422

(PIN)		RS-422	RS-485
1	T/R+	(A+)	RS-485 (A+)
2	T/R-	(B-)	RS-485 (B-)
3	RXD+	(A+)	
4	RXD-	(B-)	
5	GND2		

(PIN)		
1	PGND	
2	V-	
3	V+	(9~30VDC)

## UT-509D

RS-485 RS-422  
T/R+T/R- A+  
/B- RXD+/RXD- +/ Ž V+ V-  
PGND T/R+ T/R- RXD+ RXD-  
T/R-  
UT-509D  
1 /  
2 /  
3 /  
4 /

120 1/4W



